



TECHNICAL DATA

MASSES

Basic mass (without battery)	80 Kg
Operating mass (BOB10)	89.3 kg

COMPACTION

Frequency	98 Hz
Centrifugal force	20 kN

TRACTION

Max. gradeability	46 %
Max. working speed	25 m/min

ELECTRICAL SYSTEM

Battery type	Lithium-ion
Nominal battery voltage	51 V
IP Rating	IP23

DRIVE SYSTEM


Drive system	Direct drive eccentric motor
Nominal power	1.2 kW

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.



DIMENSIONS



DIMENSIONS

H. Height	556 mm
H1. Height, standard handle	961 mm
H2. Height, standard handle	1045 mm
L. Length	630 mm
L1. Length	1060 mm
W. Basic plate width	500 mm

STANDARD FEATURES OPTIONAL EQUIPMENT

- Easy start/stop system
- Low vibration handle
- Plug and play battery docking
- One point lifting
- Direct drive motor
- Comfort handle with Ergo Grip
- Low HAV levels

- Additional battery
Batteryone BOB5
Batteryone BOB10
Batteryone BOB14
- Additional charger
Batteryone BOC7
Batteryone BOC13
- Synthetic mat
- Transport wheels

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.